



Van Dyck

CLAY PAVIORS



COLOUR, CHARACTER, TEXTURE, FLEXIBILITY,
AVAILABILITY, INNOVATION. BUT ABOVE ALL QUALITY.



Van Dyck

CLAY PAVIORS




CASTLEYARD

Also available in:



HADLEY RED MIXTURE



CHARCOAL MIXTURE

Advantages

- Naturally attractive
- Provide the character of old 'stone sett' paving
- Permanent non-fade colours
- Simple to install
- Easy to maintain
- Resistant to staining (petrol, oil, acids etc)
- Improves kerb appeal especially for buildings and developments of character
- Nil efflorescence
- Good slipping, skidding and abrasion resistance
- Totally durable
- Can be readily uplifted and re-laid to provide access to underground services
- Full range of complementary pavior accessories and 'cobbles' available
- Competitively priced

APPLICATIONS

Suitable for pedestrian and lightly trafficked applications when laid in a running bond pattern. For heavy traffic, 240 x 120 x 65mm Van Dyck paviors should be used in a herringbone bond pattern.

COVERAGE

Individual sizes of Van Dyck paviors are supplied in separate packs and should be randomly blended in equal proportions (1:1:1) on site. A set of three different sized paviors covers an area of 0.067m². When used in equal proportions 15 paviors of each size are required to cover 1m².

ON SITE REQUIREMENTS

120 x 120 x 65mm paviors are supplied as 'blocks' of two paviors. Before laying, the 'blocks' should be broken down into individual units by striking them with a 'brick hammer'.

Technical Data

Work Size: 240 x 120 x 65mm
200 x 120 x 65mm
120 x 120 x 65mm

Pavior Classification: Type PB

Texture: Wirecut

Transverse Breaking Load: Greater than 7KN

Liability to Efflorescence: Nil

Frost Resistance: Frost resistant (F)

Quantity per pack:
(240 x 120 x 65mm) 348
(200 x 120 x 65mm) 348
(120 x 120 x 65mm) 696

Where appropriate the above information is determined in accordance with the requirements of BS 3921:1985.

Pavior Accessories



Fig 7
Kerb

Cant
Kerb



Channel
Unit




Buckfast
Kerb



Information in this leaflet is provided for guidance only. Due to the limitations of photography and printing, the colours and textures illustrated are for use as a guide only. Actual samples are available on request.

Blockleys Brick Ltd. reserves the right to amend specifications and prices at any time without prior notice, in the pursuit of continuous product development.

Blockleys Brick Limited is part of the Michelmersh Group of Companies



BLOCKLEYS BRICK LIMITED

Sommerfeld Road, Trench Lock,
Telford, Shropshire TF1 5RY

Telephone: 01952 251933

Fax: 01952 265377

Email: sales@blockleys.com

Website: www.blockleys.com